

REOTRON SMP-KMA

Installation on mounting wall



Unique Selling Point

- Very good cos PHI of 0,95
- Power Factor Correction
- Compact dimensions
- Series or parallel connection
- Air or water cooled
- Many options of combinations for different requirements with other
- REO product ranges

Description

The REOTRON SMP power supplies are primary switched power supplies with galvanic separation from the input to the output. They can be used as voltage, current or power regulators.

Operation

The unit can be operated from an internal display, external control signals of 0...+10V, 0(4)...20mA or optionally by a fieldbus interface such as DeviceNet, ProfiBus, CanBus, EtherCAT, EtherNet/IP and ProfiNet protocols.

Input devices

The device input is designed for connection to a three-phase mains 3 x 400 V, 50/60 Hz. The compliance of EMC standards is guaranteed by an input-sided PFC-mains filter.

Design

The devices have a compact design in a 19 inch rackmount chassis and can be delivered as a installation ready control cabinet version or as a tabletop unit (lab version). The devices are air- or water-cooled.

Connection

The SMP's are connected via screw terminals and with cooper terminal buses at high output currents. Like all REO-products, the REOTRON SMP's are also available as customized versions.

High range of performance

The units can be combined to power supplies with higher ratings by connecting the units in series or parallel.

Technical Data

- Output voltage : 10 - 50 V
- Output Current : 2 - 7,5 A
- Output power : 20 - 200 W

REOTRON SMP-KMA

Installation on mounting wall

Technical Data

Type	REOTRON SMP-KMA
Input voltage:	230 V, +/- 10 %, 50/60 Hz
Ripple p-p:	100 mV/200 mV
Setpoint Input:	0...+10 V, DC 0(4)...20 mA, Potentiometer 10 kOhm internal control over display
Actual Output:	0...+10 V, DC 0(4)...20 mA, internal control over display
Interfaces (optional)	DeviceNet, ProfiBus, CanBus, EtherCAT, EtherNet/IP, ProfiNet
Control accuracy:	1% of the nominal value (higher on request)
Rating:	24 V, DC or contact
Protection:	Cabinet installation IP 20
2 x relay status:	Changer 250 V, 1A
Efficiency:	> 85 %
Cos Φ :	0,95
PFC:	0,94
Operating temperature:	0...+45 °C
Standards:	EN 50178, EN 61000-6-2, EN 61000-6-4

REOTRON SMP-KMA

Installation on mounting wall

REO Series	SMP-KMA 10-2	SMP-KMA 10-5	SMP-KMA 10-7,5	SMP-KMA 20-2	SMP-KMA 20-5	SMP-KMA 24-5
Output power [W]	0...20	0...50	0...75	0...40	0...100	0...120
Output voltage [V]	0...10	0...10	0...10	0...20	0...20	0...24
Output current [A]	0...2	0...5	0...7,5	0...2	0...5	0...5
Dimensions [BxHxT]	120x238x177	120x238x177	120x238x177	120x238x177	120x238x177	120x238x177

REO Series	SMP-KMA 30-2	SMP-KMA 40-2
Output power [W]	0...60	0...80
Output voltage [V]	0...30	0...40
Output current [A]	0...2	0...2
Dimensions [BxHxT]	120x238x177	120x238x177

Dimension drawing

