

# REOMED 800W

*Wide range input for the Medical Technology*



## Unique Selling Point

- IEC 60601-1 (ed 3.1)
- IEC 60601-1-2 (ed 4.0)
- Certificated according to NRTL
- Optional shield winding between primary and secondary current
- Variants with filter and surge protection
- High efficiency with a very low magnetic field
- Wide range of options
- Small weight
- Short-circuit and overload protection
- Integral start-up current limiter
- Solid aluminum casing
- Eupipotential bonding pin DIN 42801
- Output sockets EN 60320

## Description

The TÜV-certified REOMED isolating transformers are proven and reliable equipment for use with all electrical systems in a medical environment. They reduce the leakage current and thus help to ensure the safety of patients.

REOMED isolating transformers are characterized by their very low magnetic stray-fields and reliability, whilst also providing high efficiency and easy connectivity.

Application area:

- Medical systems

## Technical Data

- Rated power : 800 VA
- Input voltage : 100-130/200-250 V

Type	H (mm)	B (mm)	T (mm)	Weightt (kg)
REOMED 800W	100 (105*)	220	300	12,5

\* with rubber feet

# REOMED 800W

*Wide range input for the Medical Technology*

REOMED	800W
Nominal input power [VA]	800
Input voltage [V]	100-130/200-250
Output voltage [V]	100-130/200-250
Mains frequency [Hz]	50/60
Input power plug	1 piece IE C/EN 60320 (C14) UL 498, CSA C22.2 no. 42
Output power plug	9 piece IEC/EN60320-2-2 (C13) UL 498 CSA C22.2 no. 42
Power switch [0-1]	yes
Input fuse [A]	T8/T4
Thermal overload protection [°C]	120
Max. output current [A]	8,00-6,16 / 4,00-3,20
Output fuse [A]	-
Start-up current limiter	yes
Standard	electronic
Earth leakage current 127/254V [µA]	<300/500
Insulation / protection resistance [Ω]	>2M/<0,1
Test voltage	primary-secondary: 4kV AC; primary housing / secondary housing: 1,5kV AC
Protection class/med. class/Type	I/I
Protection IP	IP20
Ambient temperature [°C]	±0 ... +40
Ambient air humidity [%]	Relative 30 - 75
Max. altitude [m/feet]	3000/9864
Equi-potential earthing (DIN42801)	POAG - S6/15
Housing, Surface	Powder-coated metal - RAL 7035
Dimensions (BxHxT) [mm/in]	220x100*x300 (*with rubber feet 105)/8.66x3.94*x11.81 (*with rubber feet4.13)
Weight [kg/lbs]	12,5/27.5
Approval / principles / Conformity CE	IEC60601-1:2005/AMD1:2012; ANSI/AAMIES 60601-1:2005/CR/2012 CAN/CSA C22.2 No. 60601-1:14 (Medical) USA and Canada IEC60601-1-2:2014(Partly); EN/IEC 61000-3-2:2014; EN/IEC 61000-3-3:2013
Accessories (Options)	
Power line	Country-specific
Mounting rails	Mounting kit (2x mounting rails, 4x hexagon screw)