




























# Overview UL-listed products

## UL-CERTIFIED PRODUCTS INSULATION SYSTEM CLASS B (130 ° C) E217179

	1-phase mains chokes		3-phase mains choke								Motor chokes		Sinusoidal filter	
														
	<b>CNW 901</b>	<b>CNW M 901</b>	<b>CNW 903</b>	<b>CNW 903</b>	<b>CNW M 903</b>	<b>CNW M 903</b>	<b>CNW 905</b>	<b>CNW M 905</b>	<b>CNW 906</b>	<b>CNW M 906</b>	<b>CNW 854</b>	<b>CNW M 854</b>	<b>CNW 933</b>	<b>CNW M 933</b>
Rated current	2 - 45A	2 -50 A	3 -32,4 A	6/ 10/ 17,1 A	3 -32,4 A	6/ 10/ 17,1 A	3 - 28A	3 - 28 A	3 - 34 A	3 - 34 A	1,8- 43,2 A	1,8- 43,2 A	1,8 - 36 A	1,8 - 36 A
Rated voltage	250 V	250 V	500 V	600 V	500 V	600 V	500 V	500 V	500 V	500 V	500 V	500 V	500 V	500 V
Construction	open	encasted	open	open	encasted	encasted	open	encasted	open	open	open	encasted	open	encasted
Voltage drop	UK 4%	UK 4%	UK 4%	UK 4%	UK 4%	UK 4%	UK 2%	UK 2%	UK 1%	UK 1%			Uk 8%	Uk 8%
Max. ambient temp.	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C	40°C
Insulation class	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)	B (130°C)
UL category	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR	NMTR
Certificate Number	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179	E217179

	1-phase mains filter		3-phase mains filter, single stage				two stage		Medical transformers						
															
	<b>CNW 101</b>	<b>CNW 102</b>	<b>CNW 103</b>	<b>CNW 114</b>	<b>CNW 203</b>	<b>CNW 104</b>	<b>CNW 204</b>	<b>REOMED I</b>	<b>REOMED I</b>	<b>REOMED W</b>	<b>REOMED II</b>				
Rated current	3 - 20 A	3 - 20 A	3 - 150 A	8 - 600 A	16 - 30 A	6	7 - 42 A								
Rated voltage	250 V	250 V	500 V	500 V	480 V	440 V	480 V								
Attenuation	high	very high	high	very high	high	very high	very high								
UL category	FOKY2	FOKY2	FOKY2	FOKY2	FOKY2	FOKY2	FOKY2								
CertificateNumber	E217177	E217177	E217177	E217177	E217177	E217177	E217177								
								Rated power	300, 600, 800,1000 VA	1300, 1600,2200 VA	300, 800 VA	660,1120,			
								Input voltage	115-230 V	115-230 V	100-130/200-250 V	1580,2000 VA			
								TÜV SÜD	NRTL	NRTL	NRTL	230 V			
									3rd	3rd	3rd	TÜV SÜD			

	Compact resistors				Register braking resistors
					
	<b>BW 151</b>	<b>BW 153</b>	<b>BW 156</b>	<b>BW 156/Combination</b>	<b>BW 605</b>
Rated power	50 - 300 W	100 - 400 W	400 - 1500 W	2000 - 7500 W	2000 -5000 W
Rated voltage	900V DC / 600VAC	900V DC / 600V AC	900V DC / 600V AC	900V DC / 600V AC	400 V
Degree of protection	IP 20/40/ 54	IP 20/40/54	IP 20/40/54	IP 20	IP 22
UL category	NMTR2	NMTR2	NMTR2	NMTR2	NMMS2
Certificate Number	E217179	E217179	E217179	E217179	E217180

# Overview UL-listed products



OVERVIEW PRODUCTS BY INSULATION SYSTEM REO AG E251513 CLASS 130 (B) - B1, CLASS 155 (F) - REO 155-1, CLASS 155 (F) - REO 203-1, CLASS 180 (H) - REO 342-1 ; CLASS 220 (H) - REO 220

## Chokes

## AC Magnets

CNW, CNW M	CNW, CNW M	CNW, CNW M	CNW, CNW M	CNW, CNW M	WI/WE
Class 130 (B) offen vergossen 40°C B (130°C) OBJY2 E251513	Class 155 (F) offen vergossen 40°C F (155°C) OBJY2 E251513	Class 155 (F) offen vergossen 40°C F (155°C) OBJY2 E251513	Class 180 (H) offen vergossen 40°C H (180°C) OBJY2 E251513	Class 180 (H) offen 40°C H (180°C) OBJY2 E251513	Class 130 (B) vergossen 40°C B (130°C) OBJY2 E251513

Insulation system  
Construction  
Construction  
Max. ambient temp.  
Insulation class  
UL category  
Certificate Number



## UL-listed Products of REO



## REOVIB Frequency converters

MFS 268	MFS 268	MFS 268	MFS 268 Accessories
3/6/8/16 A 110/230 V IP 20 NMTR E217179	6/8/12/16 A 110/230 V IP 54 NMTR E217179	16 A 110/230 V IP 20 NMTR E217179	Interfaces: DP, DN, CAN, RS, NFA, EC, EIP, compact ND  REOVIB MFS 268 Adapter cable for 24V , DC - signal input / output model (s) Signal I / O 4pol. - M12 , signal I / O 5pol. -M12  REOVIB MFS 268-IP54-PV 6, 8, 12, 16 A: Adapter cable for input and output sockets

Output current  
Power input  
IP protection  
UL category  
Certification Number



REO AG

Brühler Straße 100 · D-42657 Solingen  
Tel.: +49 (0)212 8804 0 · Fax: +49 (0)212 8804 188

E-Mail: info@reo.de  
Internet: www.reo.de

Pure|Power|Perfection